

Temperature Monitoring at Licensed Compost Facilities

PUB-WA1585
May 2012



Waste & Materials Management
P.O. Box 7921
Madison, WI 53707-7921

INTRODUCTION

When done properly, the composting process significantly reduces the incidence of harmful pathogens in the finished product. Wisconsin's new composting regulations (NR 502.12, Wis. Adm. Code), effective June 1, 2012, require operators of licensed compost facilities to **monitor temperatures** during the composting process, and to **keep records of temperatures and turning events**. Turning piles and windrows and maintaining correct temperatures will ensure that any disease-causing bacteria, viruses and other pathogens are minimized, and enable the operator to demonstrate that the compost was made properly.

BACKGROUND

The raw materials used in composting can contain harmful microorganisms, and other pathogens can be introduced during composting by birds and other wild animals. To protect the ultimate users of the compost you produce, it is necessary to take steps to reduce this risk. Properly functioning compost accomplishes this through the self-heating mechanism that compost undergoes as it decomposes. The heating is enhanced by optimal moisture conditions and distributed through the entire batch by periodic mixing, or "turning."

Over the years, the compost industry has determined the amount and duration of heating that is needed to minimize pathogens in the final product. These guidelines are different for different composting methods:

- For the most common method of composting, **windrows and static piles**, attain a minimum temperature of 55°C (131°F) on a minimum of 15 days (not necessarily consecutive) and turn the windrows or piles at least 5 times during the high-temperature periods.
- For **in-vessel or mechanically aerated static piles** (i.e., using a blower to force air through the pile), maintain a continuous minimum temperature of 55°C (131°F) for 3 consecutive days (72 hours).

METHODS

To measure compost temperatures, you will need a long-probe thermometer (generally 4 feet in length) to obtain readings from the core of the windrow or static pile. It is important to establish consistent technique and locations for taking temperature measurements from an active windrow or static pile. **Make every effort to obtain temperature measurements representative of the entire batch of compost.**

Location: Ideally, two temperatures should be taken at each location: a near surface temperature about 12 inches below the surface, and a core temperature taken 4 feet or more into the compost pile. Typically these routine temperature readings are taken about 4 feet off the ground. To obtain a more complete sense of the conditions in the compost, temperature readings should be obtained from both the "cool" (typically north) and "warm" (typically south) sides of the windrow.

Number of measurements: Taking temperatures every 150 linear feet of windrow (about every 50 paces) or every 200 cubic yards will provide a very complete indication of temperature conditions. However, not every facility can afford to take this many readings. A minimum of 6 evenly spaced measurements taken per pile, windrow, or vessel provides basic data on temperatures for management purposes.

Frequency: Temperature readings provide a quick assessment of the status of the biological processes in an active compost windrow. Initially, temperature readings fluctuate as optimal moisture and oxygen conditions are established. At a minimum, weekly temperature readings should be used to track and adjust these conditions. Temperatures taken daily during the period when pathogen reduction temperatures are being achieved (when temperatures have attained 55°C or 131°F) are the best way to verify that pathogen reduction is taking place.

Recordkeeping: Temperatures and turning events should be logged on a spreadsheet. An example field log (please feel free to adapt this for the specifics of your facility) is attached to this fact sheet.

Records Retention: Temperature and turning records should be maintained at the compost facility for one year.

A NOTE ON MOISTURE

Moisture content is an easily monitored condition that, when incorrect, may lead to the loss of oxygen within the compost, reduced compost temperatures and the development of odors. The ideal moisture level for an active compost pile is 50%. This is most easily monitored by the “squeeze test”. Squeeze test means to dig into the compost pile, grab a handful, and squeeze. If the pile is too wet, you will squeeze water out. If the pile is too dry, the clump will break apart when you open your hand and release the pressure.

Contact 608/266-2111 or DNRWasteMaterials@wisconsin.gov for further information.

Disclaimers: This document is intended solely as guidance and does not include any mandatory requirements except where requirements found in statute or administrative rule are referenced. This guidance does not establish or affect legal rights or obligations and is not finally determinative of any of the issues addressed. This guidance does not create any rights enforceable by any party in litigation with the State of Wisconsin or the Department of Natural Resources. Any regulatory decisions made by the Department of Natural Resources in any manner addressed by this guidance will be made by applying the governing statutes and administrative rules to the relevant facts.

The Wisconsin Department of Natural Resources provides equal opportunity in its employment, programs, services and functions under an Affirmative Action Plan. If you have any questions, please write to Equal Opportunity Office, Department of the Interior, Washington, D.C. 20240. This publication is available in alternative format (large print, Braille, audio tape, etc.) upon request. Please call 608/266-2111 for more information.

Compost Facility Field Monitoring Form
 Pile or Windrow ID: _____

Point A: _____
 Point B: _____

Point C: _____
 Point D: _____

Point E: _____
 Point F: _____

Date	Process Day	ID (initials)	Outside Temp.	Time	Depth	Compost Temperatures						Notes (turning events, moisture conditions/adjustments or odors)
						A	B	C	D	E	F	
					12"							
					48"							
					12"							
					48"							
					12"							
					48"							
					12"							
					48"							
					12"							
					48"							
					12"							
					48"							
					12"							
					48"							